

## ACE134419B

### P-Channel Enhancement Mode Power MOSFET

### **Description**

- DC/DC Converters in Computing, servers, POL
- Isolated DC/DC Converters in Telecom and Industrial

### **Features**

- V<sub>DS</sub> (V) = -30V
- $I_D = -29.5A$
- $R_{DS(ON)}$ @  $V_{GS}$ = -10V, TYP 14m $\Omega$
- $R_{DS(ON})$ @  $V_{GS}$ = -4.5V, TYP 19.5m $\Omega$

## **Absolute Maximum Ratings**

Abootato maximum ratingo					
Parameter		Symbol	Max	Unit	
Drain-Source Voltage		$V_{DS}$	-30	V	
Gate-Source Voltage		$V_{GS}$	±20	V	
Drain Current (Continuous) *AC	T <sub>C</sub> =25 °C	- I <sub>D</sub>	-29.5	A	
	T <sub>C</sub> =70 °C		-23.6		
Drain Current (Pulse) *B		I <sub>DM</sub>	-120		
Power Dissipation	T <sub>C</sub> =25 °C	$P_{D}$	25	W	
Operating and Storage Temperature Range		T <sub>J</sub> /T <sub>STG</sub>	-55 to 150	°C	

A: The value of  $R_{\theta JA}$  is measured with the device mounted on  $1\text{in}^2$  FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^{\circ}\text{C}$ . The value in any given application depends on the user's specific board design.

- B: Repetitive rating, pulse width limited by junction temperature.
- C: The current rating is based on the t≤ 10s junction to ambient thermal resistance rating.

### **Thermal Resistance Ratings**


Parameter		Symbol	Maximum	Unit
Maximum Junction-to-Ambient	t≤10s	$R_{thJA}$	50	°C/W
Maximum Junction-to-Case (Drain)	Steady State	$R_{thJC}$	5	



# ACE134419B

## P-Channel Enhancement Mode Power MOSFET

## **Ordering information**





### ACE134419B

### P-Channel Enhancement Mode Power MOSFET

#### Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Technology Co., LTD. As sued herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and shoes failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
- A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ACE Technology Co., LTD. http://www.ace-ele.com/