



ACE14614B

60V Complementary Enhancement Mode Power MOSFET

Description

- used in inverter
- other applications

Features

N-Channel

- $V_{DS}=60V$
- $I_D=5.2A$
- $R_{DS(ON)}@V_{GS}=10V$, TYP 27 m Ω
- $R_{DS(ON)}@V_{GS}=4.5V$, TYP 34 m Ω

P-Channel

- $V_{DS}= -60V$
- $I_D=-4.2A$
- $R_{DS(ON)}@V_{GS}= -10V$, TYP 50 m Ω
- $R_{DS(ON)}@V_{GS}= -4.5V$, TYP 62 m Ω

Absolute Maximum Ratings

Parameter		Symbol	N-Ratings	P-Ratings	Unit
Drain-Source Voltage		V_{DSS}	40	-60	V
Gate-Source Voltage		V_{GSS}	± 20	± 20	V
Drain Current (Continuous) *AC	$T_A=25^\circ C$	I_D	5.2	-4.2	A
	$T_A=70^\circ C$		4.1	-3.4	
Drain Current (Pulse) *B		I_{DM}	21	-17	A
Power Dissipation	$T_A=25^\circ C$	P_D	2		W
Operating Temperature/ Storage Temperature		T_J/T_{STG}	-55~150	-55~150	$^\circ C$

Note :

- The value of $R_{\theta JA}$ is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ C$. The value in any given application depends on the user's specific board design.
- Repetitive rating, pulse width limited by junction temperature.
- The current rating is based on the $t \leq 10s$ junction to ambient thermal resistance rating

Thermal Resistance Ratings


Parameter		Symbol	Maximum	Units
Maximum Junction-to-Ambient	$t \leq 10s$	R_{thJA}	48	$^\circ C/W$
Maximum Junction-to Lead	Steady State	R_{thJL}	35	$^\circ C/W$



ACE14614B


60V Complementary Enhancement Mode Power MOSFET

Packaging Type



Ordering information

ACE14614B XX + H





ACE14614B

60V Complementary Enhancement Mode Power MOSFET

Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Technology Co., LTD.

As sued herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ACE Technology Co., LTD.
<http://www.ace-ele.com/>