



# ACE7212Y

## High-Efficiency 2A Continuous 24V Input Synchronous Step Down Converter

### Description

The ACE7212Y is high-efficiency, high frequency synchronous step-down DC-DC regulator ICs capable of delivering up to 2A continuous output currents. The ACE7212Y family operate over a wide input voltage range from 4.5V to 24V and integrate main switch and synchronous switch with very low  $R_{DS(ON)}$  to minimize the conduction loss.

ACE7212Y adopts the COT architecture to achieve fast transient responses for high step-down applications and high efficiency at light loads. In addition, it operates at pseudo-constant frequency of 500kHz under heavy load conditions to minimize the size of inductor and capacitor.

### Features

- Low  $R_{DS(ON)}$  for internal switches (top/bottom) 130m $\Omega$ /90m $\Omega$ , 2.0A DC current
- 4.5-24V input voltage range
- High-Efficiency Synchronous-Mode
- Internal soft start limits the inrush current
- Over Current protection
- Thermal shutdown
- Green package:
- SOT23-6 is pin compatible.

### Application

- Portable Navigation Device
- Set Top Box
- Portable TV
- LCD TV



# ACE7212Y

## High-Efficiency 2A Continuous 24V Input Synchronous Step Down Converter

### Absolute Maximum Ratings

Parameter		Rating	Unit
Supply Voltage (V+ – V-)		28	V
EN, LX Voltage		$V_{IN}+0.3$	V
FB, BS Voltage		4	V
Power Dissipation, $P_D$ @ $T_A = 25^\circ\text{C}$ , SOT-23-6		0.6	W
Package Thermal Resistance	$\Theta_{JA}$	170	$^\circ\text{C/W}$
	$\Theta_{JC}$	130	
Storage Temperature Range		-65 to 150	$^\circ\text{C}$
Junction Temperature Range		150	$^\circ\text{C}$
Lead Temperature Range		260	$^\circ\text{C}$
HBM ESD, JESD22-A114	VIN Pin	$\pm 1$	kV
	Other Pins	$\pm 2$	

Stresses beyond those listed under “Absolute Maximum Rating” may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other condition beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

### Recommended Work Conditions


Parameter	Rating	Unit
Supply Voltage	4.5 to 24	V
Junction Temperature Range	-40 to 125	$^\circ\text{C}$
Ambient Temperature Range	-40 to 85	$^\circ\text{C}$

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended Operating conditions are specified to ensure optimal performance to the datasheet specifications.




# ACE7212Y High-Efficiency 2A Continuous 24V Input Synchronous Step Down Converter

## Packaging Type



## Ordering information

ACE7212Y XX+ H





#### Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Technology Co., LTD. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.