



ACE735N

High Efficiency, 1.5A 40V Input Synchronous Step-Down Regulator

Description

ACE735N develops a high efficiency synchronous step-down DC-DC converter capable of delivering 1A load current. The ACE735N operate over a wide input voltage range from 4.5V to 40V and integrate main switch and synchronous switch with low $R_{DS(ON)}$ to minimize the conduction loss.

The ACE735N adopts peak current control scheme. The switching frequency is 2MHz. Low output voltage ripple and small external inductor and capacitor sizes are achieved with 2MHz switching frequency.

The device also features ultra low quiescent operating to achieve high efficiency under light load. And the internal soft-start limits inrush current during power on.

Features

- Low $R_{DS(ON)}$ for Internal Switches
(Top/Bottom):380m Ω /180m Ω
- 4.5-40V Input Voltage Range
- 2MHz Fixed Switching Frequency
- 0.8V \pm 1.0% Reference Voltage
- Low Quiescent Current
- Internal Soft-start Limits the Inrush Current
- Hic-cup Mode Output Short Circuit Protection
- Thermal Shutdown and Auto Recovery
- Compact Package: SOT23-6

Applications

- LCD-TV
- Set Top Box
- Notebook
- Storage
- High Power AP Router
- Networking



ACE735N

High Efficiency, 1.5A 40V Input Synchronous Step-Down Regulator

Absolute Maximum Ratings ^(Note1)

Parameter		Value
Supply Input Voltage		-0.3 to 40V
SW, FB, EN Voltage		-0.3 to 40V
BST-SW Voltage		-0.3 to 4V
Power Dissipation, PD@T _A =25°C		0.4 W
Package Thermal Resistance ^(Note 2)	θ_{JA}	100°C/W
	θ_{JC}	30°C/W
Junction Temperature Range		-40°C to 150°C
Lead Temperature (Soldering, 10sec.)		260°C
Storage Temperature Range		-65°C to 150°C
Dynamic SW Voltage in 10ns Duration		IN+3V to GND -5V

Note 1: Stresses beyond the “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Note 2: Package thermal resistance is measured in the natural convection at T_A = 25°C.

Recommended Operating Conditions ^(Note 3)

Parameter	Value
Supply Input Voltage	4.5V to 40V
Junction Temperature Range	-40°C to 125°C
Ambient Temperature Range	-40°C to 85°C

Note 3: The device is not guaranteed to function outside its operating conditions.




ACE735N

High Efficiency, 1.5A 40V Input Synchronous Step-Down Regulator

Ordering information

ACE735N XX + H





ACE735N

High Efficiency, 1.5A 40V Input Synchronous Step-Down Regulator

Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Technology Co., LTD. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.